

Full Light

FLIP
CHIP

投射燈/
高天井燈



Powered by WLCSP Technology

 晟安光電股份有限公司
 總公司: 台中市西屯區工業41路30號
 電話: 886-4-23591122
 傳真: 886-4-23501177
 地址: 台中市西屯區工業41路30號
 廠址: 台中市西屯區工業41路30號
 產品名稱: LED投射燈
 燈具型號: DHS 100W
 燈具功率: 100W
 燈具電壓: 17-0384-01
 燈具電流: 17-0384-01
 光學規格型號: LED 50W
 每顆光學光通量(lm)
 光學數量: 2
 發光面積(mm): 286
 測試模式: C
 電壓(V): 220-0100
 電流(A): 0.4720
 功率(W): 100.2800
 功率因數: 0.9670
 額定電壓: F54W36V1500*2PCS
 發光面積(mm): 256
 發光高度(mm): 80
 光度結果
 燈具光通量(lm): 10237.27
 燈具效率(lm/w): 102.09
 中心光強(cd): 3735.537
 最大光強(cd): 3740.111
 最大光強角度: C=85.0 y=0.0
 半峰通角(50%Imax): [C0]180]Left=59.1 Right=56.6
 [C90]270]Left=57.6 Right=56.7
 光束擴散角(10%Imax): [C0]180]Left=73.4 Right=72.8
 [C90]270]Left=63.3 Right=68.2

CCT: 5700K CRI: 70%	投射燈	Power consumption	Luminous flux	Angle	IP	Size (mm)/ Weight (kg)
	FLG50W-57CW	50W	5000Lm ±8%	120	66	245x210x70 ≐1.6 kg
	FLG100W-57CW	100W	10000Lm ±8%	120	66	286x256x80 ≐3.0 kg
	FLG150W-57CW	150W	15000Lm ±8%	120	66	360x315x90 ≐4.0 kg

CCT: 5700K CRI: 70%	輕型高井燈	Power consumption	Luminous flux	Angle	IP	Size (mm)/ Weight (kg)
	HBD100W-57CW	100W	11500Lm ±10%	45/60/90 /120		Φ410 H:360 ≐2.5 kg
	HBD150W-57CW	150W	17250Lm ±10%	45/60/90 /120		Φ410 H:360 ≐2.8 kg
	HBE200W-57CW	200W	23000Lm ±10%	45/60/90 /120		Φ490 H:462 ≐4.1 kg
	HBE250W-57CW	250W	28750Lm ±10%	45/60/90 /120		Φ490 H:462 ≐4.4 kg



**DH 110
300-1000W**



**DH 6357
150-400W**



**DH 4238
30-200W**



***接受客製生產**
本公司保有燈具修飾權

晟安光電股份有限公司

Full Light

Powered by WLCSP Technology



CE

TAF

RoHS
COMPLIANT

免焊線專利晶片及製程LED不良率減少90%



晟安光電股份有限公司
40768 台中市西屯區工業41路30號
統一編號: 80606894
TEL: 886 4 2359 1122
FAX: 886 4 2350 1177

