



BD263

## Add-on block 2P 63A 30mA HI

Product Datasheet

### Architecture

Neutral position	left
Number of poles	2 P

### Main electrical features

Rated operational voltage U <sub>e</sub>	230 V
Frequency	50 Hz

### Voltage

Rated insulation voltage	500 V
Rated impulse withstand voltage	4000 V

### Electric current

Rated residual operating current	30 mA
Rated current	63 A

### Electric current / temperature

Rating current 40°C	63 A
---------------------	------

### Frequency

Frequency	50 Hz
-----------	-------

### Power

Total power loss under I <sub>N</sub>	4,4 W
---------------------------------------	-------

### Tripping

Protected against nuisance tripping	yes
-------------------------------------	-----

### Endurance

Electric endurance in number of cycles	2000
Number of mechanical operations	2000

### Dimensions

Depth of installed product	9,2 cm
Height of installed product	7 cm
Width of installed product	3,5 cm

### Installation, mounting

Tightening torque	2,8Nm
Type of top rail clip for modular devices	Plastic
Type of bottom rail clip for modular devices	NA
Top removability for modular devices	yes
Bottom removability for modular devices	no

## Connection

Connection cross-sect. flexible conductor	16mm <sup>2</sup>
Connection cross-sect. rigid cable	25mm <sup>2</sup>

## Settings

Rated fault current adjustable	no
Delay adjustable	no

## Standards

European directive WEEE	concerned
-------------------------	-----------

## Safety

Protection index IP	IP20
Residual current type	HI

## Use conditions

Operating temperature	-5...40 °C
Altitude	2000 m
Air humidity protection	Execution I

FONLEE  
豐立自動控制器材有限公司  
www.fonlee.com.tw