

HH-Sicherungseinsätze


HV - Fuse Links

HH 1 – 03/00

Mit Temperatur-Begrenzer

With Temperature-Limiter

QUALITÄTSMANAGEMENTSYSTEM



DQS-zertifiziert nach
DIN EN ISO 9001 - Reg.-Nr. 19 182



SICHERUNGEN/FUSES



HV-Back-up fuse links

| Operating voltage U_n kV | Rated current I_n A | Dimensions | | Part No. | Rated breaking current I_a / kA | Minimum breaking current I_{mn} / A | Cold resistance R_k / mOhm | Power loss P_V / W | kg |
|----------------------------------|-----------------------------|------------|---------|-----------|--------------------------------------------|------------------------------------------------|------------------------------------|----------------------------|-----|
| | | "e" mm | d mm | | | | | | |
| 3 - 7,2 | *200 | 292 | 85 | 30 100 14 | 50 | 800 | 1,9 | 134 | 3,8 |
| | *250 | | | | | 1000 | 1,6 | 191 | |
| | *315 | | | | | 1260 | 1,2 | 281 | |
| | *355 | | | | | 1420 | 1 | 336 | |
| | *400 | 442 | 85 | 30 110 14 | 50 | 1600 | 1,1 | 347 | |
| | *500 | | | | | 2000 | 0,85 | 430 | |

(*) please observe derating factors . Special documentation on request.

