

Receptacles – Panel mounted, with screw terminals

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request. For drawings and dimensions see page 105 - 117.
Products with pilot contact available on request.



Panel mounted receptacle
flange 75 x 75 mm, straight

IP 44
Std. Pack. Qty: 10
Drawing: 1 MB 464

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
16	3	1365	1366	1367		3054 3055
16	4	1388	1389	1390	1391	1392 1393
16	5	1384	1386	1385	3057	3059 3060
32	3	1394	1395	1396		
32	4	1397	1398	1399	1400	1401 1402
32	5	3449	3454	3451	3452	3455 3447



Panel mounted receptacle
X-CONTACT, flange 107 x 110 mm,
straight

IP 44
Std. Pack. Qty: 5
Drawing: 1 MB 211

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
63	3	1260A	1261A			
63	4		1247A	1248A	1249A	
63	5			1252A		



Panel mounted receptacle
flange 16 A, 3 p: 73.5 x 64 mm,
16 A, 4 + 5 p, 32 A: 100 x 92 mm,
inclination 20°, 32 A: receptacles
optional fitted with auxiliary contact

IP 44
Std. Pack. Qty: 10
Drawing: 1 MB 260

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
16	3	1462	1463	1464		3186 3187
16	4	1465	1466	1467	1468	1469 1470
16	5	1471	1472	1473	3188	3189 3190
32	3	1491	1492	1493		3201 3202
32	4	1494	1495	1496	1497	1486 1487
32	5	1498	1499	1500	3191	3192 3193



Panel mounted receptacle
X-CONTACT, flange 110 x 106 mm,
inclination 20°

IP 44
Std. Pack. Qty: 5
Drawing: 1 MB 297

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
63	3	1146A	1147A	1148A		
63	4	1149A	1150A	1151A	1152A	
63	5	1153A	1154A	1155A		



Panel mounted receptacle
63 A: X-CONTACT, standard flange
dimensions, uniform fixing hole
spacing, 15° inclination for 16 A and
32 A, 20° inclination for 63 A

IP 44
Std. Pack. Qty: 5
Drawing: 1 MB 453

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
16	5			20146A		
32	5			20147A		
63	5			21160A		



Panel mounted receptacle
miniflange: 68 x 62 mm,
inclination 20°

IP 44
Std. Pack. Qty: 10
Drawing: 1 MB 472

A	P	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	>50 - 500 V 100-300 Hz 300-500 Hz
16	3	858	857			